



2240. DIN 73379-3E Fuel Hose

A black rubber textile reinforced hose for conveying commercial fuels. Suitable for Petrol in mixture with up to 100% Methanol, Ethanol & Butanol E100. Diesel in mixture with up to 100% Rapeseed Methyl Ester, Hydro Treated Vegetable Oil, fatty Acid Methyl Ester & Soya Methyl Ester.



- Construction: Cover: Black smooth ECO.
 Reinforcement: High tensile Aramid synthetic textile plies.
 Liner: Black smooth FKM.
- Temperature: -40°C to +125°C
- Identification: COHLINE-2240. *Size Code- Size mm x mm- > FPM/ECO/AR/ECO<* Date Stamp.
- Safety Factor: 5:1 (Burst pressure 5 times working pressure).

| Part Number | Bore (mm) | Outside Diameter (mm) | Working Pressure (Bar) | Minimum Bend Radius (mm) |
|--------------|-----------|-----------------------|------------------------|--------------------------|
| IH-2240.0209 | 3.2 | 9.0 | 10 | 30 |
| IH-2240.0400 | 5.5 | 11.5 | 10 | 55 |
| IH-2240.0600 | 7.3 | 13.5 | 10 | 60 |
| IH-2240.0800 | 9.3 | 15.3 | 10 | 70 |
| IH-2240.1000 | 11.5 | 18.5 | 10 | 80 |
| IH-2192.1000 | 14.0 | 22.0 | 10 | 100 |